

2017-8222
2018-08-22

USE LIMITATION:

Treatment facilities shall provide appropriate industrial hygiene measures and safety equipment for the safe use of this product. The treatment site must have effective containment and pollution abatement technology to insure that the pesticide is not released into the surrounding environment under normal operating conditions. Freshly treated wood shall be handled and stored in a manner which provides no opportunity for the preservative release into the environment. Outdoor treatment facilities are prohibited.

DIRECTIONS FOR USE:

Post a copy of this label in the treatment area.

For the protection of wood joinery products against decay and moulds. The requirements of applicable laws should be determined before using the product Do not dilute this product. As this product is not registered for the control of pests in aquatic systems, **DO NOT** use to control aquatic pests.

For use on wood joinery products including window and door components or exterior non-structural decorative wood joinery items which are not found in ground contact. Do not use on wood products which may come in contact with food, feed or drinking water. Machine cut, glue and sand wood as desired prior to treating. Do not apply over previously painted, stained or otherwise coated wood. Wood must be clean and dry. Apply at temperatures above 4 °C and below 25°C. Engineered ventilation systems may be required to remove solvent vapours during treatment, mixing or drying.

DO NOT contaminate irrigation or drinking water supplies or aquatic habitats by cleaning of equipment or disposal of wastes.

Apply this product by the following methods:

Double vacuum system (closed systems). Target volumetric retention rate of propiconazole: 60g/m³. Wood should be dry to the touch upon removal from the treating chamber. Use a treating schedule which achieves adequate distribution of propiconazole to meet market standards or customer specifications.

Bundle Dipping or other immersion methods which utilizes automated technology (3 minute minimum treatment). Target deposition rate of propiconazole: 0.12g/m².

Flood Coating, Roller Coating or Flow Coating using automated technology (15 second minimum treatment). Target deposition rate of propiconazole: 0.12g/m².

Spray Box automated technology (treating parameters appropriate for the specific unit and substrate). Target deposition rate of propiconazole: 0.08g/m².

Finishing:

Prior to top-coating with paint, varnish or other materials the wood must be free of residual solvent. Allow four to eight hours at an ambient temperature, 20 °C; accelerated drying methods may be used to reduce drying time.

Clean up: Use mineral spirits to remove wood preservative from contaminated surfaces.

DO NOT contaminate irrigation or drinking water supplies or aquatic habitats by cleaning of equipment or disposal of wastes.

This product is **TOXIC** to aquatic organisms. It is not to be used in circumstances that would cause or allow it to enter lakes, streams, ponds, estuaries, oceans or other waters in contravention of federal or provincial regulatory requirements. The requirements of applicable laws should be determined before using the product.

DRYVAC® 1010

WATER REPELLENT WOOD PRESERVATIVE

For INDUSTRIAL Use
SOLUTION

ACTIVE INGREDIENT: Propiconazole 0.5%
READ THE LABEL BEFORE USING
KEEP OUT OF REACH OF CHILDREN



CAUTION – POISON
TOXIC to aquatic organisms

SKIN IRRITANT
POTENTIAL SKIN SENSITIZER

Warning: contains the allergen soy

REGISTRATION NO. 24246
PEST CONTROL PRODUCTS ACT

NET CONTENTS: 18.9L to 15000L

EVERDRY FOREST PRODUCTS LTD
PO BOX 1174
Guelph ON N1H 6N3
(905) 842-6411

DRYVAC® 1010

PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN

Post a copy of this label in the treatment area.

Potential skin sensitizer. Harmful if swallowed, inhaled or absorbed through the skin. May cause eye and skin irritation.

- Avoid breathing of vapor or spray mist. Avoid contact with skin, eyes and clothing.
- Wear chemical-resistant coveralls over long-sleeved shirt and long pants, chemical resistant gloves, goggles or face shield, socks, and chemical-resistant footwear when handling the concentrate or during mixing/loading, clean-up, maintenance and repair activities.
- Use a NIOSH-respirator if the area is not well ventilated or if airborne exposure levels are above the occupational exposure limit(s), as determined by air sampling.
- Use a NIOSH-respirator during clean-up, maintenance and repair activities when working in/on application equipment or if airborne material (e.g. dust, mist/spray) may be generated when working in the treatment area.
- Use a NIOSH-respirator when opening pressure treatment cylinder doors.
- When handling freshly treated wood, handling treated wood that has not fully dried, or if there is a potential for getting wet by the treating solution during other activities, wear chemical-resistant coveralls or a chemical-resistant apron over long-sleeved shirt and long pants, chemical-resistant gloves, socks and chemical-resistant footwear.
- When working in the application area, wear long-sleeved shirt, long pants, chemical-resistant gloves, socks and boots. Wear goggles or face shield if there is a possibility of splashing.
- Once dry, the treated wood can be handled with cotton or leather gloves.
- Wash hands and face before eating, drinking, smoking and using the toilet. Change clothes daily. Wash contaminated clothing separately from household laundry. Not for use or storage in or around the home. Clean contaminated equipment thoroughly prior to making welding repairs.

FIRST AID:

If Swallowed: Call a poison control centre or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

If on skin/clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control centre or doctor for treatment advice.

If In Eyes: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice.

If Inhaled: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice.

Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

TOXICOLOGICAL INFORMATION: No specific antidote known. This product contains a petroleum distillate. Vomiting may cause aspiration pneumonia. Treat symptomatically.

2017-8222
2018-08-22

Dip tanks and drip aprons must be roofed, paved and drained to prevent dilution and loss of treatment solution.
Store treated lumber on a channeled drip pan until dripping has ceased. Slope lumber on the drip pad to expedite drainage and to ensure that no puddles remain on the surface of the wood.
Manage drippage and other related wastes to prevent release in the environment.
DO NOT expose treated lumber to rains immediately after treatment.
For further information on storage, handling, and disposal of treated wood, contact the manufacturer of this product or the provincial regulatory agency.

STORAGE AND DISPOSAL:

Storage:

To prevent contamination, store this product away from food or feed. Store in the original closed and labeled container in a cool place. Keep containers closed when not in use. Store above 0°C. Do not store on unpaved surfaces.

Disposal:

For recyclable containers:

DO NOT reuse this container for any other purpose. This is a recyclable container, and is to be disposed of at a container collection site. Contact your local distributor/dealer or municipality for the location of the nearest collection site. Before taking the container to the collection site:

- 1) Triple- or pressure rinse the empty container. Dispose of the rinsings in accordance with provincial requirements.
- 2) Make the empty, rinsed container unsuitable for further use. If there is no container collection site in your area, dispose of the container in accordance with provincial requirements.

For information on disposal of unused, unwanted product, or in the case of a spill or spill clean-up, contact the manufacturer or the provincial regulatory agency.

For returnable containers:

DO NOT reuse returnable containers for any purpose. Returnable containers should be returned to the manufacturing plant; contact manufacturer for details. They must be refilled by the manufacturer with the same product. Do not reuse these containers for any other purpose.

For containers that can be refilled for the user by the distributor/dealer:

This container may be returned to the point of purchase (distributor/dealer). It must be refilled by the distributor/dealer with the same product. Do not reuse this container for any other purpose.

WATER REPELLENT WOOD PRESERVATIVE

For INDUSTRIAL Use
SOLUTION

ACTIVE INGREDIENT: Propiconazole 0.5%



CAUTION – POISON
TOXIC to aquatic organisms

SKIN IRRITANT
POTENTIAL SKIN SENSITIZER

Warning: contains the allergen soy

REGISTRATION NO. 24246
PEST CONTROL PRODUCTS ACT

NET CONTENTS: 18.9L to 15000L

EVERDRY FOREST PRODUCTS LTD
PO BOX 1174
Guelph ON N1H 6N3
(905) 842-6411

PHYSICAL AND CHEMICAL HAZARDS: Do not use or store near heat or open flame. In case of fire, use water spray, foam, carbon dioxide or dry chemical. Keep from freezing. Store above 0°C.

ENVIRONMENTAL PRECAUTIONS: This product is **TOXIC** to aquatic organisms and non-target terrestrial plants. Avoid contamination of aquatic systems during application. Do not contaminate these systems by direct application, disposal of waste or cleaning equipment. The product contains a petroleum distillate; avoid contact with soil during application or storage.

NOTICE TO USER:

This pest control product is to be used only in accordance with the directions on the label. It is an offence under the Pest Control Products Act to use this product in a way that is inconsistent with the directions on the label.